

# PREMIER

# ITP-84 S

## SHARED TRAITS

- .Color : Silver
- .Operating environment: Temperature(0~45 °C) Humidity(RH 10~80%)
- .Storage environment: Temperature(-10 ~ 60°C) Humidity (RH 10 ~ 80%)
- .Dimensions : 152×134×125 mm (D×W×H)
- .Weight: 0,84 Kg
- .Masterbox units: 12



## DATASHEET

MODEL	ITP-84 S
Printing method	Direct thermal
Connectivity	USB+Serie+Lan
Print speed	260 mm/seg
Paper width	80 mm
Line spacing	3.75mm (adjustable via commands)
Column capacity	576 points/line
Character size	ANK, Font A: 1.5 × 3.0 mm (12 × 24 dots) / Font B: 1.1 × 2.1 mm (9 × 17 dots) / Chinese, Traditional Chinese: 3.0 × 3.0 mm (24 × 24 dots)
Character extension	PC347 (European standard), Katakana, PC850 (Multilingual), PC860 (Portuguese), PC863 (Canadian French), PC865 (Nordic), Western Europe, Greek, Hebrew, Eastern Europe, Iran, WPC1252, PC866 (Cyrillic #2), PC852 (Latin 2), PC858, Iran II, Latvian, Arabic, PT151 (1251)
1D code	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128
2D code	QR code / PDF417
Buffer	4096 Kbytes
NV Flash	256 KB
Power supply	Input 100V~240V / Output 24V/2.5A
Consumption	50~60Hz
Drawer output	DC 24V/1A
Cutter type	Partial
Cutter life	1.5 million
Printhead life	150Km
Emulation	ESC/POS
Supported OS	Windows/JPOS/OPOS/Linux/Android