

PREMIER

ILP-108 Portable BT



SHARED TRAITS

- Color : Gray
- Operating environment: Temperature(-10~45) Humidity(25~85% without condensation)
- Storage environment: Temperature(-40~60C) Humidity(10~90% without condensation)
- Dimensions : 150x131x64mm (LxWxH)
- Weight: 583 g

DATASHEET

MODEL	ILP-108 Portable BT
Printing method	Direct thermal
Connectivity	USB + Bluetooth
Resolution	203 ppp
Print speed	100 mm/seg
Paper width	40mm ~ 112mm
Maximum print length	1778 mm (70")
Print area	104 mm
Maximum roll diameter	φ50 mm
Paper thickness	0,06 mm ~0,254 mm
Screen	13 inch OLED
Sensor	Gap sensor / Cover open sensor / Black mark sensor
Internal fonts	8 alphanumeric bitmap fonts, Windows fonts can be downloaded from the software
1D code	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5)-digit add-on, MSI, PLESSEY, POSTNET, China POST
2D code	PDF-417, Maxicode, DataMatrix, código QR, Aztec
Rotation	0°, 90°, 180°, 270°
CPU	32 bit
Buffer	8 MB
NV Flash	8 MB
Power supply	Output 5V-2A
Battery	7.4V / 2500 mAh
Printhead life	30 Km
Emulation	TSPL, EPL, ZPL, DPL, CPCL, ESC/POS