PREMIER

# ILP-500+





## SHARED TRAITS

·Color : Dark gray

.Operating environment: Temperature(5~40)  Humidity(25~85% without condensation)

.Storage environment: Temperature(-40~60C) Humidity(10~90% without condensation)

·Dimensions : 282mmx232mmx171mm (DxWxH)

.Weight: 2.56 kg

## DATASHEET

| MODEL | ILP-500+ |
|---|---|
| Printing method | Direct thermal and thermal transfer |
| Connectivity | USB + LAN |
| Resolution | 203 ppp |
| Print speed | 152 mm/seg |
| Paper width | 127 mm (external diameter) x 25,4 mm (core inner diameter) |
| Maximum print length | 10 mm ~ 1778 mm |
| Print area | 104 mm |
| Maximum roll diameter | 67 mm |
| Paper thickness | 0,06 mm ~0,254 mm |
| Sensor | Movable black mark sensor / Movable gap sensor |
| Internal fonts | Font 0 ~ Font 8 |
| 1D code | Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5)-digit add-on, MSI, PLESSEY, POSTNET, China POST, GS1 DataBar, Code 11 |
| 2D code | PDF-417, Maxicode, DataMatrix, QR code, Aztec |
| Buffer | 8 MB |
| NV Flash | 8 MB |
| Printhead life | 30 Km or 1 year |
| Emulation | TSPL, ZPL, EPL, DPL |
| Supported OS | Windows /Linux /Mac / Android / Chrome |
| SDK | Windows/Linux/Android/iOS |