

PREMIER

ITP-58 BT



Model	ITP-58 BT
Color:	Black
Printing method:	Direct thermal
Paper width:	58 mm
Print width:	48 mm
Paper roll diameter:	≤ 30 mm
Printing speed:	80 mm/s Max.
Interface:	USB + Serial + Bluetooth
Line spacing:	3.75 mm (adjustable by commands)
Column number:	58mm paper: Font A - 32 columns/Font B - 42 columns / Chinese, traditional Chinese - 16 columns
Character size:	ANK, Font A: 1.5x3.0mm (12x24 dots) Font B: 1.1x2.1mm (9x17 dots) simplified/traditional Chinese: 3.0x3.0mm (24x24 dots)
Resolution:	203 dpi
Extension character sheet:	PC347 (Standard Europe), Katakana, PC850 (Multilingual), PC860 (Portuguese), PC863 (Canadian-French), PC865 (Nordic), West Europe, Greek, Hebrew, East Europe, Iran, WPC1252, PC866 (Cyrillic#2), PC852 (Latin2), PC858, IranII, Latvian, Arabic, PT151 (1251)
1D Barcode:	UPC-A/UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODE39/ITF/CODABAR/CODE93/CODE128
2D Barcode:	QR Code / PDF417
Input buffer:	32 Kbytes
NV Flash:	64 Kbytes
Power supply:	AC 110V/240V, 50~60Hz
Power source:	Output: DC 9V-2A
Cash drawer:	DC 24V/1A
Weight:	0.22 Kg
Dimensions:	111 x 88 x 41 mm (DxWxH)
Work environment:	Temperature (0~45°C) Humidity RH (10~80%)
Storage environment:	Temperature (-10~60°C) Humidity RH (10~90%) no condensation
Printer head life:	50 Km