

# PREMIER

## ILP-108 Portable BT



Model	ILP-108 Portable BT
Color:	Grey
Printing method:	Direct thermal
Resolution:	203 DPI
Printing speed:	100 mm/s Max.
Print width:	105 mm
Print length:	1778 mm
Media type:	Continuous, gap, black mark
Media width:	40 mm - 112 mm
Media thickness:	0.06 mm - 0.254 mm
Label roll diameter:	50 mm
Processor:	32-bit CPU
Memory:	8MB Flash Memory/ 8MB SDRAM
Interface:	USB + Bluetooth
Screen:	OLED (1.3")
Sensors:	1. Gap sensor / 2. Cover opening sensor / 3. Black mark sensor
Internal fonts:	8 alpha-numeric bitmap fonts, Windows fonts are downloadable from software
1D Barcode:	Code 39, Code 93, Code 128UCC, Code 128 subsets A, B, C, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, EAN and UPC 2(5) digits add-on, MSI, PLESSEY, POSTNET, China POST
2D Barcode:	PDF-417, Maxicode, DataMatrix, QR code, Aztec
Rotation:	0°, 90°, 180°, 270°
Emulation:	TSPL, EPL, ZPL, DPL, CPCL, ESC/POS

Dimension:	150 x 131 x 64 mm (LxWxH)
Weight:	3583 gr
Print head life:	30 Km
Operation system:	Windows/Android/iOS
SDK:	Windows/Android/iOS
Input/Output:	Input: AC 100-240V,0.5A 50-60Hz / Output:DC 9V/1A
Battery:	2500mAh Li-ion
Operation environment:	Temperature (10~45°C) Humidity (25~85% no condensing)
Storage environment:	Temperature (40~60°C) Humidity RH (10~90% no condensing)