

PREMIER

ITP-85 Beeper

SHARED TRAITS

- Color : Black
- Operating environment: Temperature (0~45 °C) Humidity (10~80 °C)
- Storage environment: Temperature (-10~60 °C) Humidity (10~90 °C)
- Dimensions : 168x130x123.5mm (DxWxH)
- Weight: 0.89 Kg
- Masterbox units: 6



DATASHEET

MODEL	ITP-85 Beeper
Printing method	Direct thermal
Connectivity	USB+Lan+Wifi
Print speed	230 mm/seg
Paper width	79.5±0.5 mm
Print area	72mm
Line spacing	3.75mm (adjustable via commands)
Maximum roll diameter	φ80 mm
Column capacity	576 points/line o 512 points/line
Character size	ANK, Font A: 1.5 × 3.0 mm (12 × 24 dots) / Font B: 1.1 × 2.1 mm (9 × 17 dots) / Chinese, Traditional Chinese: 3.0 × 3.0 mm (24 × 24 dots)
Character extension	PC347 (European standard), Katakana, PC850 (Multilingual), PC860 (Portuguese), PC863 (Canadian French), PC865 (Nordic), Western Europe, Greek, Hebrew, Eastern Europe, Iran, WPC1252, PC866 (Cyrillic #2), PC852 (Latin 2), PC858, Iran II, Latvian, Arabic, PT151 (1251)
1D code	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128
2D code	QR code / PDF417
Buffer	256 KB
NV Flash	256 KB
Power supply	Input 110~240V / Output 24V-2.5A
Consumption	50~60Hz
Drawer output	DC 24V/1A
Cutter type	Partial
Cutter life	1.5 million
Printhead life	150Km
Emulation	ESC/POS
Supported OS	Windows/Linux/Mac/Android