



Model	ITP-58 II
Color:	Black
Printing method:	Direct thermal
Paper width:	57.5 ± 0.5 mm
Print width:	48 mm
Column capacity:	384 dots/line (adjustable by command)
Printing speed:	90 mm/s Max.
Interface:	USB
Line spacing:	3.75 mm (adjustable by commands)
Character size:	Font A: 12x24, Font B: 9x17, CHN: 24x24
Characters line:	Font A: 32 chars Font B: 42 chars CHN: 16 Character Sets
1D Barcode:	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128
Input buffer:	32 Kbytes
NV Flash:	64 Kbytes
Power adaptor:	AC 110V/220V, 50~60Hz Output : DC 12V/2.6A
Power source:	DC 12V/2.6A
Cash drawer output:	DC 12V/1A
Dimensions:	181 x 130 x 111.2 mm (DxWxH)
Weight:	0.56 Kg
Work environment:	Temperature (0~45°C) Humidity (10~80°C)
Storage environment:	Temperature (10~60°C) Humidity (10~90°C)
Printer head life:	50 Km
Emulation:	ESC/POS
Driver:	Windows/Linux/Android/Mac
Utility:	Windows & Linux test Utility
SDK:	iOS/Android/Windows
Warranty:	3 years