

PREMIER

MS3-1D



Model	MS3-1D (with stand)
Color:	Black
Interface:	USB
CPU:	32 bits ARM
Light source:	Visible Laser 650 mm
Decoding capacity:	Codabar, Code 93, Code1 28, UCC/EAN-128, Code 39, EAN-8, EAN-13, UPC-A, ISBN, Industrial 25, Standard 25, 2/5 Matrix, ect.
Trigger mode:	Trigger buttons, continuous scanning
Sensing distance:	15 cm (100 cm ²)
Resolution:	Minium 3 mils
Depth of scanning:	2-9 cm (0,1 mm bar width), 3-50 cm (0,3 mm bar width)
Decoding speed:	150 times/sec
Bar width:	50-30 cm
Prompting mode:	Buzzer, indicator light
Printing contrast:	30%
Scan angles:	Roll 30°, pitch 75°, yaw 65°
Cylinder horizontal scanning:	Diameter 35mm
IP Grade:	IP42
Materials:	ABS + PC
Power supply:	DC 5V ± 5%
Operating temperature:	0 - 50°C / 32 - 122°F
Operating humidity:	20 - 85% (non-condensing)
Dimensions:	185 x 67 x 54 mm
Weight:	110 ± 5 g (including cable)
Warranty:	3 years