

# PREMIER

## ITP-85 Beeper



Model	ITP-85 Beeper
Printing method:	Direct Thermal
Media width:	79.5 ± 0.5 mm / Ø 80 mm
Print width:	72 mm
Column capacity:	576 dots/line or 512 dots/line
Printing speed:	260 mm/s
Interface:	USB   Lan   Wifi
Line spacing:	3.75 mm (Adjustable by commands)
Character size:	ANK, Font A: 1.5 x 3.0 mm (12 x 24 dots) Font B: 1.1 x 2.1 mm (9x17 dots) Simplified/Traditional Chinese: 3.0 x 3.0 mm (24 x 24 dots)
Extension character sheet:	PC437(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portugal) / PC863(Canadian) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran/WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / PC858 / IranII / Latvian / Arabic / PT151(1251)
1D Barcode:	UPC-A/UPC-E/JAN13(EAN13)/JAN8(EAN8)/CODE39/ITF/CODABAR/ CODE93/CODE128
2D Barcode:	QR CODE / PDF417
Input buffer:	256 Kbytes
NVFlash:	256 Kbytes

# PREMIER

## ITP-85 Beeper



- 58 mm/80 mm paper width available



- Flash LED Light and big beeper voice

Power adaptor:	Input: AC 100 ~ 240V, 50 ~ 60 Hz   Output: DC 24V/2.5A
Printer Input:	DC 24V/2.5A
Cash drawer:	DC 24V/1A
Weight:	0.89 Kg
Dimensions:	168 x 130 x 123.5 mm (DxWxH)
Work environment:	Temperature (0 ~ 45 °C) humidity (10 ~ 80 %)
Storage environment:	Temperature (-10 ~ 60 °C) humidity (10 ~ 90 %)
Auto cutter:	Partial
Cutter life:	1.5 million cuts
Printer head life:	150 Km
Emulation:	ESC / POS
Driver:	Windows / Linux / Mac OS / Android

