

# PREMIER

# ITP-58 BT

## SHARED TRAITS

- Color : Black
- Operating environment: Temperature(0~45) Humidity(10~90%)
- Storage environment: Temperature(-10~60C) Humidity(10~90%)
- Dimensions : 111×88×41 mm(DxWxH)
- Weight: 0.22 Kg



## DATASHEET

MODEL	ITP-58 BT
Printing method	Direct thermal
Connectivity	USB+Serie+Bluetooth
Resolution	203 ppp
Print speed	80 mm/seg
Paper width	58 mm
Print area	48mm
Line spacing	3.75mm (adjustable via commands)
Maximum roll diameter	φ30 mm
Column number	58 mm paper: Font A - 32 columns / Font B - 42 columns / Chinese, Traditional Chinese - 16 columns
Character size	ANK, Font A: 1.5 × 3.0 mm (12 × 24 dots) Font B: 1.1 × 2.1 mm (9 × 17 dots) Chinese, Traditional Chinese: 3.0 × 3.0 mm (24 × 24 dots)
Character extension	PC347 (European standard), Katakana, PC850 (Multilingual), PC860 (Portuguese), PC863 (Canadian French), PC865 (Nordic), Western Europe, Greek, Hebrew, Eastern Europe, Iran, WPC1252, PC866 (Cyrillic #2), PC852 (Latin2), PC858, Iran II, Latvian, Arabic, PT151 (1251)
1D code	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128
2D code	QR code / PDF417
Buffer	32 KB
NV Flash	64 MB
Power supply	Input 110V~240V / Output 9V-2A
Consumption	50~60Hz
Printhead life	50Km