

# PREMIER

# ITP-Front II

## SHARED TRAITS

- Color : Black
- Operating environment: Temperature(0~45) Humidity(10~80%)
- Storage environment: Temperature(-10~60C) Humidity(10~90%)
- Dimensions : 134 x 130 x 132mm (D\*W\*H)
- Weight: 0.9 Kg
- Masterbox units: 12



## DATASHEET

MODEL	ITP-Front II
Printing method	Direct thermal
Connectivity	USB+Serial+LAN+WIFI
Resolution	203 DPI
Print speed	230 mm/sec
Paper width	79.5/ 57.5 ±0,5 mm
Print area	72 mm/ 48 mm
Line spacing	3.75mm (adjustable via commands)
Paper roll diameter	80mm ± 0.5mm
Column capacity	576 points/line
Character size	ANK, Font A: 1.5 × 3.0 mm (12 × 24 dots), Font B: 1.1 × 2.1 mm (9 × 17 dots) Chinese, Traditional Chinese: 3.0 × 3.0 mm (24 × 24 dots)
Character extension	PC347 (European Standard), Katakana, PC850 (Multilingual), PC860 (Portuguese), PC863 (Canadian French), PC865 (Nordic), Western European, Greek, Hebrew, Eastern European, Iran, WPC1252, PC866 (Cyrillic #2), PC852 (Latin 2), PC858, Iran II, Latvian, Arabic, PT151 (1251)
1D Code	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128
2D Code	QR CODE / PDF417
Buffer	96 KB
NV Flash	256 KB
Power supply	Input 100~240V
Consumption	50~60Hz
Drawer output	DC 24V/1A
Cutter type	Partial
Cutter life	1.5 million
Printhead life	150Kmm
Emulation	ESC/POS
Supported OS	Windows/Linux/Android/Mac